

KEMPER 460^{PRO}, 475^{PRO} & 490^{PRO} Corn Heads

Built for clean crop flow, uptime, and confidence in tough conditions.

When harvest windows get tight, your header must keep up. Kemper 400^{PRO} Series corn heads are built for operators who need reliable feeding, clean cutting, and smooth crop flow through changing field conditions.

Why Customers Choose KEMPER

1. Handles changing field conditions

Row-independent harvesting and high-speed mowing rotors support clean cutting across the working width, even in difficult crops.

2. Keeps crop moving smoothly

Transverse feeding drums consolidate the crop for even feeding toward the cutterhead.

3. Built for uptime and value

Robust construction, resistant materials, and low maintenance needs help protect your investment.

4. Ready for the road

All three models fold for transport — 9.8 ft (3.00 m) wide, or 10.8 ft (3.30 m) on the 475^{PRO}

Model Comparison



Specification	460 ^{PRO}	475 ^{PRO}	490 ^{PRO}
Working width	20 ft. (6.00 m)	25 ft. (7.50 m)	30 ft. (9.00 m)
Transport width	9.8 ft. (3.00 m)	10.8 ft. (3.30 m)	9.8 ft. (3.00 m)
Overall width	19.7 ft. (6.00 m)	24.8 ft. (7.55 m)	29.6 ft. (9.02 m)
Length	8.5 ft. (2.60 m)	9.1 ft. (2.78 m)	8.9 ft. (2.70 m)
Height	5.9 ft. (1.81 m)	5.0 ft. (1.52 m)	6.3 ft. (1.92 m)
Weight	6,393 lbs. (2,900 kg)	7,937 lbs. (3,600 kg)	9,590 lbs. (4,350 kg)

Height shown in working position. Specifications per KEMPER 400^{PRO} Series data.